

PATCO *Air Tools*

Manufacturer of Quality Air Tools and Components

Global Link Tools
A division of Patco

www.patcoairtools.com

AG-2312

1/4" RIGHT ANGLE DIE GRINDER

Features a hardened alloy steel cylinder and rotor to maintain power while ensuring longer tool life. Contains tough alloy steel pinion & bevel gear transmission design for smooth, quiet operation. Motor housing milled from solid aluminum bar stock for precision alignment. Comes with a 1/4" double angle 300 series collet and two collet wrenches.



Horse Power	0.3
Exhaust	Rear
Free Speed	12000 RPM
Collet Size	1/4"
Air Inlet	1/4"
Height	2.86"
Overall Length	5.80"
Weight	1.12 lbs.

Compatible with DOTCO: 10L1280-36

AG-2320

1/4" RIGHT ANGLE DIE GRINDER

Features a hardened alloy steel cylinder and rotor to maintain power while ensuring longer tool life. Contains tough alloy steel pinion & bevel gear transmission design for smooth, quiet operation. Motor housing milled from solid aluminum bar stock for precision alignment. Comes with a 1/4" double angle 300 series collet and two collet wrenches.



Horse Power	0.3
Exhaust	Rear
Free Speed	20000 RPM
Collet Size	1/4"
Air Inlet	1/4"
Height	2.86"
Overall Length	5.80"
Weight	1.12 lbs.

Compatible with DOTCO: 10L1281-36

DE-2350

1/4" STRAIGHT DIE GRINDER

Features a hardened alloy steel cylinder and rotor to maintain power while ensuring longer tool life. Motor housing milled from solid aluminum bar stock for precision alignment. Comes with a 1/4" double angle 300 series collet and two collet wrenches.



Horse Power	0.3
Exhaust	Rear
Free Speed	25000 RPM
Collet Size	1/4"
Air Inlet	1/4"
Height	1.34"
Overall Length	9.15"
Weight	1.30 lbs.

Compatible with DOTCO: 10L1180-36

DE-2550

1/4" STRAIGHT DIE GRINDER

Features a hardened alloy steel cylinder and rotor to maintain power while ensuring longer tool life. Motor housing milled from solid aluminum bar stock for precision alignment. Comes with a 1/4" double angle 300 series collet and two collet wrenches.



Horse Power	0.3
Exhaust	Rear
Free Speed	25000 RPM
Collet Size	1/4"
Air Inlet	1/4"
Height	1.34"
Overall Length	11.15"
Weight	1.50 lbs

Compatible with DOTCO: 10L1181-36

DE-2750

1/4" STRAIGHT DIE GRINDER

Features a hardened alloy steel cylinder and rotor to maintain power while ensuring longer tool life. Motor housing milled from solid aluminum bar stock for precision alignment. Comes with a 1/4" double angle 300 series collet and two collet wrenches.



Horse Power	0.3
Exhaust	Rear
Free Speed	25000 RPM
Collet Size	1/4"
Air Inlet	1/4"
Height	1.34"
Overall Length	13.15"
Weight	1.70 lbs.

DG-2350

1/4" STRAIGHT DIE GRINDER

Features a hardened alloy steel cylinder and rotor to maintain power while ensuring longer tool life. Motor housing milled from solid aluminum bar stock for precision alignment. Comes with a 1/4" double angle 300 series collet and two collet wrenches.



Horse Power	0.3
Exhaust	Rear
Free Speed	25000 RPM
Collet Size	1/4"
Air Inlet	1/4"
Height	1.34"
Overall Length	5.64"
Weight	0.82 lbs.

Compatible with DOTCO: 10L1082-36

VG3-7600

VERTICAL GRINDER - WITH GUARD

Designed for use with quick change Type 27 threaded hub wheels. Wheel not included. Ideal for heavy-duty grinding for smoothing; finishing, removing scale, rust and weld splatter; cleaning castings and masonry work. Features safety lever, hardened steel motor parts and corrosion resistant governor.

Optional 6", 9" and cup wheel guards available. 1100-200 2" End Wrench (included)

Capacity	7"
Free Speed	6000 RPM
Spindle Thread	5/8"-11
Maximum HP	3.00
Height	7-5/8"
Weight	9.45 lbs.
Rec'd Hose Size	1/2"
Air Inlet Thread	1/2"

Compatible with TOPCAT 54V



VG4-9600

VERTICAL GRINDER - WITH GUARD

Designed for use with quick change Type 27 threaded hub wheels. Wheel not included. Ideal for heavy-duty grinding for smoothing; finishing, removing scale, rust and weld splatter; cleaning castings and masonry work. Features safety lever, hardened steel motor parts and corrosion resistant governor.

Optional cup wheel guards available. 1100-200 2" End Wrench (included)

Capacity	9"
Free Speed	6000 RPM
Spindle Thread	5/8"-11
Maximum HP	4.00
Height	8-3/16"
Weight	10.9 lbs.
Rec'd Hose Size	1/2"
Air Inlet Thread	1/2"

Compatible with TOPCAT 64V



CHP-4BM-H & CHP-4BM-R

MINI 4-BOLT CHIPPING HAMMER

Two-step piston design, the Mini 4-Bolt is ideal for cleaning castings and forgings, as well as refractory, gunite and brick work. Hits harder than any other 10 lb. chipping hammer currently on the market.

Please specify .580 hex or .680 round shank.



Blows Per Minute	2750
Stroke	2.6"
Bore	1.1"
Length	14-1/4"
Weight	10.5 lbs.
Air Inlet Thread	3/8" or 7/8" -24

CTE-100

CARBIDE TIP ENGRAVER

Ideal for writing on a variety of materials such as steel up to RC64, glass, plastic and wood with precision. Lightweight and durable.



Tool Length	5"
Throttle Sleeve	Graduated
Weight	5 oz.
Inlet	1/8" NPT
Hose I.D	1/4"
Hose Length	5'
CFM	1

Compatible with most CP-9361 Parts

Notes

Patco Air Tools Warranty and Terms

WARRANTY

All **PATCO Air Tools, Inc.** pneumatic power tools are rigorously inspected and performance tested in our factory before shipping to our customers. If an inherent defect is found during normal use and service, **PATCO Air Tools, Inc.** will warrant this tool against defects in workmanship and materials for the first year of the tool. In the instances **PATCO Air Tools, Inc.** tools develops a performance problem, simply return the tool, transportation prepaid with your name, address and dated proof of purchase, along with a brief explanation of the defect. Upon examination and review at our factory, **PATCO Air Tools, Inc.** shall confirm that the tool qualifies for warranty status, and will repair or replace the tool at no charge to the customer. This warranty constitutes the entire obligation of **PATCO Air Tools, Inc.** relating to the sale of such product and its maximum liability is limited to the purchase price of such product. In no event shall **PATCO Air Tools, Inc.** be held liable for incidental, indirect, consequential or special damage of any kind arising from the sale or use of such product.

All parts considered wearable parts and products are NOT covered under this warranty. Examples of wearable items include, but not limited to bearings, contact wheels, rotor blades, regulators, valve stems, levers, shrouds, guards, O-rings, seals and gaskets.

PATCO Air Tools, Inc.'s warranty policy is contingent upon proper use of our tools in accordance with factory recommendations, instructions, and safety practices. It shall not apply to equipment that has been subjected to misuse, negligence, accident or tampering in any way so as to affect its normal performance.

MERCHANDISE RETURNS

All returns must receive prior approval from **PATCO Air Tools, Inc.** and display a Returned Merchandise Authorization number. All authorized returns will receive credit upon validation as new merchandise in saleable condition. No merchandise will be authorized for return if used, abused, or modified in any way, unless under the terms of warranty. All returns are subject to a 20% restocking fee.

CREDIT TERMS

Upon credit approval, all new accounts are subject to credit terms of net 30 with no interest. Any accounts 31 days in arrears are subject to credit watch, and any accounts 45 days in arrears will be placed on credit hold.

MINIMUM ORDERS

All orders are subject to a \$30 net minimum. No order will be invoiced for less than \$30.



100 Engelwood Drive, Suite G • Orion, MI 48359
Toll Free 1.800.727.2201 • 248.648.8830
Fax: 248.648.8833 • www.patcoairtools.com